

PREMIUM ASPHALT AND GREEN CONCRETE WET BLADES


WEL-CO Premium Asphalt and Green Concrete Blades are manufactured with a high concentration of high quality diamonds. They are designed to be used on high horsepower saws for the fastest cut and lowest cost in production sawing.

A wide choice of bonds and diamond depths are available to match the blade with the job. Each blade has a wide cutability range to assure versatility from job to job.



Green Concrete Specs	
GC 30	Medium to Hard Aggregate - For fast cutting and long life
GC 40	Soft to Medium Aggregate - For fast cutting and long life
Asphalt Overlay Specs	
AO 40	Hard Aggregate - For fast cutting and long life
AO 50	Soft to Medium Hard Aggregate - For fast cutting and long life
Asphalt Specs	
A 60	Medium to Hard Aggregate - For fast cutting and long life
A 70	Soft to Medium Hard Aggregate - For fast cutting and long life
A 80	Softest Aggregate - For longest life
Undercut Protection	
KS	Recommended for very abrasive cured concrete and green concrete
SS	Sweep Segment recommended for asphalt

Size	-12	-14	-16
18" x .125	\$ 738	\$ 798	\$ 858
20" x .145	\$ 924	\$ 1002	\$ 1074
26" x .160U	\$ 1272	\$ 1368	\$ 1458
30" x .175	\$ 1908	\$ 2028	\$ 2166
36" x .187	\$ 2772	\$ 2952	\$ 3132




KICKER SEGMENT (KS)
Recommended for undercutting applications such as very abrasive cured concrete and green concrete. Kicker sweep segments can be ordered by adding "KS" after the specification.



SWEEP SEGMENTS (SS)
Recommended for severe undercutting applications such as asphalt. Sweep segments can be ordered by adding "SS" after the specification.

Application	Bond	Height	Protection	Diameter	Width
A	70	- 12	SS	14 x	.125
C - Cured Concrete		Height	SS - Sweeps		
AO - Asphalt Overlay		- 12 = .375	KS - Kickers		
GC - Green Concrete		- 14 = .437			
A - Asphalt		- 16 = .500			

Example: A60-12SS 18x.125



Diamond Height