

PREMIUM WET CORE BITS

THE PREMIUM WET CORE BITS are designed for the lowest cost and fastest drilling of concrete and asphalt. Bits are available from 1/2" to 24". When ordering, add a 0, 1 or 3 after the Y to indicate the desired bond hardness. For example, the part number for a 2" asphalt bit would be: Y3-1402.000.

Additional lengths available at a cost of 5% per inch list price.



Diameter (Inches)	Part #	MSRP
1/2	Y*1000.500	\$ 158
5/8	Y*1000.625	\$ 165
3/4	Y*1000.750	\$ 173
7/8	Y*1000.875	\$ 195
1	Y*1401.000	\$ 173
1 1/8	Y*1401.125	\$ 188
1 1/4	Y*1401.250	\$ 233
1 3/8	Y*1401.375	\$ 240
1 1/2	Y*1401.500	\$ 180
1 5/8	Y*1401.625	\$ 188
1 3/4	Y*1401.750	\$ 210
1 7/8	Y*1401.875	\$ 220
2	Y*1402.000	\$ 233
2 1/4	Y*1402.250	\$ 261
2 1/2	Y*1402.500	\$ 291
2 3/4	Y*1402.750	\$ 315
3	Y*1403.000	\$ 323
3 1/4	Y*1403.250	\$ 345
3 1/2	Y*1403.500	\$ 353
4	Y*1404.000	\$ 390
4 1/4	Y*1404.250	\$ 458
4 1/2	Y*1404.500	\$ 464
5	Y*1405.000	\$ 510
5 1/2	Y*1405.500	\$ 571
6	Y*1406.000	\$ 602
6 1/4	Y*1406.250	\$ 679
6 1/2	Y*1406.500	\$ 720
7	Y*1407.000	\$ 750
8	Y*1408.000	\$ 866
9	Y*1409.000	\$ 1043
10	Y*1410.000	\$ 1163
12	Y*1512.000	\$ 1365
14	Y*1514.000	\$ 1740
16	Y*1516.000	\$ 1988
20	Y*2420.000	CALL
24	Y*2424.000	CALL

Application Specs	
Y0	Designed for fast drilling speed in cured concrete with heavy steel reinforcing or critically hard aggregate such as: Chert River Gravel Flint Quartz
Y1	Designed for drilling in cured concrete with steel reinforcing that has soft to medium aggregate such as: Granite Slate Glacial rock Limestone
Y3	Designed for drilling in green concrete or asphalt and soft abrasive materials such as: Concrete Block Asphalt

* Specify 0, 1 or 3