

PRESTRESSED WET CORE BITS

PRESTRESSED BITS are designed for drilling prestressed hollow-core. Select the correct bond. For example, the part number for drilling a 2" hole in prestressed concrete with a hard aggregate would be: P0-1402.000

Available from 1 1/2" to 6". Additional lengths available at a cost of 5% per inch list price.

Applications Specs	
P0	Designed for fast drilling speed in cured concrete with heavy steel reinforcing or critically hard aggregate
P1	Designed for drilling in cured concrete with steel reinforcing that has soft to medium aggregate



Diameter (Inches)	Part #	MSRP
1 1/2	P*1401.500	\$ 188
1 5/8	P*1401.625	N/A
1 3/4	P*1401.750	\$ 218
1 7/8	P*1401.875	\$ 225
2	P*1402.000	\$ 255
2 1/4	P*1402.250	\$ 285
2 1/2	P*1402.500	\$ 308
2 3/4	P*1402.750	\$ 330
3	P*1403.000	\$ 338
3 1/4	P*1403.250	\$ 353
3 1/2	P*1403.500	\$ 383
4	P*1404.000	\$ 413
4 1/4	P*1404.250	\$ 480
4 1/2	P*1404.500	\$ 492
5	P*1405.000	\$ 540
5 1/2	P*1405.500	\$ 630
6	P*1406.000	\$ 665

*Specify 0 or 1

Application Specs		
D1	Designed for fast dry drilling in block	
Diameter (Inches)	Part #	MSRP
1	D11001.000	\$ 173
1 1/4	D11001.250	\$ 218
1 1/2	D11001.500	\$ 180
1 3/4	D11001.750	\$ 202
2	D11002.000	\$ 233
2 1/4	D11002.250	\$ 255
2 1/2	D11002.500	\$ 270
3	D11003.000	\$ 308
3 1/2	D11003.500	\$ 345
4	D11004.000	\$ 390
4 1/2	D11004.500	\$ 413
5	D11005.000	\$ 488
6	D11006.000	\$ 570

PREMIUM DRY CORE BITS

THE PREMIUM DRY CORE BITS are designed for the lowest cost and fastest drilling of brick and block walls. Bits are available from 1" to 6".

