

STANDARD/LOW HP WET WALK BEHIND BLADES

S - STANDARD BLADES

are manufactured with high quality diamonds and are designed to be used on low horsepower saws such as electric and hydraulic. (.250" diamond height).



Cured Concrete		Size	MSRP
C 02S	Hard aggregate — For fast cutting river rock with heavy steel reinforcing	14" x .125	\$ 379
		16" x .125	\$ 431
C 06S	Medium aggregate—For fast cutting slate and glacial rock or limestone with dull sand	18" x .125	\$ 534
		18" x .145	\$ 584
C 1S	Soft aggregate—For fast cutting soft limestone with sharp sand	20" x .145	\$ 656
		24" x .160	\$ 1020
Green Concrete		26" x .160	\$ 1064
		26" x .187	\$ 1152
C 4S	Hard aggregate or long life, general purpose blade for low horsepower saws	30" x .187	\$ 1464
		36" x .187	\$ 1946



Cured Concrete with Asphalt Overlay		Size	MSRP
C 1S-SS	Hard aggregate — For fast cutting river rock with heavy steel reinforcing	14" x .125	\$ 397
		16" x .125	\$ 471
		18" x .125	\$ 561
		18" x .145	\$ 608
Asphalt		20" x .145	\$ 679
		24" x .160	\$ 1050
C 68S-SS	Hard aggregate or long life, general purpose blade for low horsepower saws	26" x .160	\$ 1093
		26" x .187	\$ 1174
		30" x .187	\$ 1495
		36" x .187	\$ 1982



SWEEP SEGMENTS (SS)

Recommended for severe undercutting applications such as asphalt. Sweep segments can be ordered by adding "SS" after the specification.