

GATOR PREMIUM SADDLE SEGMENT Wet Core Bits

Image not readable or empty
Published on Thursday, 01 November 2012 11:16 | [Print](#) | [Hits: 9437](#) | [templateId1abc/images/system/printButton.png](#)

GATOR PREMIUM SADDLE SEGMENT WET CORE BITS

WELCO'S GATOR CORE BITS provide the fastest drilling speeds in all types of cured concrete.

Their unique segment design accomplishes this by decreasing surface contact or dragwhile drilling.

These core bits are not recommended for drilling prestressedconcrete. Please reference catalog page 20 for our prestressed core bits.



Diameter (Inches)	Part #
3	G11403.000
3 1/4	G11403.250
3 1/2	G11403.500
4	G11404.000
4 1/4	G11404.250
4 1/2	G11404.500
5	G11405.000
5 1/2	G11405.500
6	G11406.000
6 1/4	G11406.250
6 1/2	G11406.500
7	G11407.000
8	G11408.000
9	G11409.000
10	G11410.000
12	G11512.000



Applications Specs	
G0	Designed for fast drilling speed in cured concrete with heavy steel reinforcing or critically hard aggregate such as: Chert River Gravel Flint Quartz
G1	Designed for drilling in cured concrete with steel reinforcing that is soft to medium aggregate such as: Granite Slate Glacial Rock Limestone