


Premium - Wet Core Bits

Image not readable or empty

Published on Thursday, 01 November 2012 14:01 | [Print](#) | [Hits: 10731](#) | 

Premium - Wet Core Bits

The Premium Wet Core Bits are designed for the lowest cost and fastest drilling of concrete and asphalt. Bits are available from 1/2" to 24". When ordering, add a 0, 1 or 3 after the Y to indicate the desired bond hardness. For example, the part number for a 2" asphalt bit would be: Y3-1402.000.

Additional lengths available at a cost of 5% per inch list price.

Diameter (Inches)	Select Bond-hardness	Part #
1/2	Y*	1000.500
5/8	Y*	1000.625
3/4	Y*	1000.750
7/8	Y*	1000.875
1	Y*	1401.000
1 1/8	Y*	1401.125
1 1/4	Y*	1401.250
1 3/8	Y*	1401.375
1 1/2	Y*	1401.500
1 5/8	Y*	1401.625
1 3/4	Y*	1401.750
1 7/8	Y*	1401.875
2	Y*	1402.000
2 1/4	Y*	1402.250
2 1/2	Y*	1402.500
2 3/4	Y*	1402.750
3	Y*	1403.000
3 1/4	Y*	1403.250
3 1/2	Y*	1403.500
4	Y*	1404.000
4 1/4	Y*	1404.250
4 1/2	Y*	1404.500
5	Y*	1405.000
5 1/2	Y*	1405.500
6	Y*	1406.000
6 1/4	Y*	1406.250
6 1/2	Y*	1406.500
7	Y*	1407.000



Application Specs - *Specify 0, 1 or 3	
Y0	<p>Designed for fast drilling speed in cured concrete with heavy steel reinforcing or critically hard aggregate such as:</p> <p>Chert River Gravel Flint Quartz</p>
Y1	<p>Designed for drilling in cured concrete with steel reinforcing that has soft to medium aggregate such as:</p> <p>Granite Slate Glacial Rock</p> <p>Limestone</p>
Y3	<p>Designed for drilling in green concrete or asphalt and soft abrasive materials such as:</p> <p>Concrete Block Asphalt</p>